

The CS002/C – Auto-Retracting Duty Safety Knife

Thank you for choosing the CS002/C Safety knife, the CS002/C has been designed to provide a duty knife which, through an Auto retracting blade maximises cut protection. Used correctly it should provide an extensive life. Detailed below are some simple measures which will help keep the user safe and achieve the best life from the knife.


User Information/Instruction Sheet

- The knife is designed to cut Films (such as Shrink Wrap, Bubble Wrap, Cellophane) Plastic Strapping, Packing Tapes, Paper and Card.
- Never modify the knife, it has been designed to have only simple blade changing maintenance, any modification could lead to sharp blades damaging people and or products and contamination of products.
- Never cut towards yourself – always cut away from the body considering others in the area.
- Never use the knife to cut materials that it has not been designed for.
- Never use the knife as a lever, it is a cutting device.
- Always report any damage to the knife and replace it immediately
- Always change the blade when it starts to become blunt (a blunt blade requires more effort, slows the operation and increases the likelihood of accidents). Consider a daily blade change for a knife in frequent use.
- Always let the blade do the work, positioned correctly a sharp blade will cut with ease; applying large effort will damage the knife and product as well as lead to more accidents.


Knife Operation

General Utility Cutting

The Auto Retracting Blade is provided for general purpose cutting. When cutting card or other resistant materials the blade should be deployed with the thumb on the side slider, after engagement in product the thumb should be released (the resistance of the material being cut will retain the blade in a cut position as long as a cut pressure is applied). When exiting the cut the blade will auto retract to its safe position. When cutting less resistant material such as films it may be necessary to hold the blade in its cut position during the cut, extra care should be taken when holding the blade in a cut position.



Blade deployed ready to engage in product



Slider released – blade still deployed



On exiting cut blade auto retracts

Blade Changing Spare Blade Ref – ERGLD354 (Straight), ERGLD254 (Straight Short)

Blade life will depend on the type of product being cut and the frequency of use, consideration for a daily blade change should be given for a knife in frequent use. Blade changing is a simple process, requiring no tools



1. Align slider with cut outs in blade guide



2. Lift Slider away from blade



3. Remove and safely dispose



4. Slide new blade into guide of the old blade (shown as Inverted for Left Hand Use)



5. Align slider with cut outs and hole in blade ensuring location



6. Release slider & check operation.